LSD600W - 6,000 ANSI LUMENS WXGA LASER INSTALLATION PROJECTOR

Key **Features**

• 3rd Generation Laser Phosphor Technology: Up to 30,000-hour maintenance-free lifespan.
• 6,000 ANSI Lumens: High-brightness performance for expansive, well-lit venues.
• Eco-Friendly Design: Consumes up to 62% less power than comparable lamp-based projectors.
• DLP 0.65" DMD Chip: Superior native contrast for deeper blacks and enhanced visual depth.
• Ultimate Installation Flexibility: 1.3x optical zoom, H/V keystone, and 360° projection.



Product **Description**

The ViewSonic® LSD600W is a powerhouse addition to the Luminous Superior Series, delivering high-brightness, lamp-free projection for corporate auditoriums, large boardrooms, and public venues. Adopting advanced 3rd generation laser phosphor technology, it provides 6,000 ANSI Lumens of consistent brightness for up to 30,000 hours, entirely eliminating the need for frequent bulb replacements and toxic mercury disposal. Designed for professional-grade reliability and sustainability, the LSD600W is 32% more compact than previous generations and features an IP5X sealed optical engine to ensure impeccable image quality in dust-prone environments. With a high-contrast 0.65" DMD chip, it delivers exceptional clarity and legibility for large-scale presentations. Its versatile setup options—including 360° orientation, and 1.3x optical zoom — make it a seamless, high-impact solution for modern installation projects.


Specifications


More Information

UPC	766907038194
Light Source	Laser
Display Resolution	WXGA (1280x800)
Display Resolution	1280 x 800
Brightness (Lumens)	6,000 ANSI
Throw Distance	0.76m - 9.95m / 2.49 ft - 32.64 ft (100"@2.54m)
Throw Ratio	1.18 - 1.54

Keystone	Vertical (± 30º) / Horizontal (± 30º)
Lens	1.3x optical zoom
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Dynamic Contrast Ratio	3,000,000:1
Aspect Ratio	16:10
Input Lag	25ms
Frequency Horizontal	15K-102KHz
Frequency Vertical	24-120Hz
USB 2.0 Type A	1 (5V/1.5A) Power, Service
3.5mm Audio Out	1
Control (RS232)	1
HDMI 1.4 (with HDCP 1.4)	2
Internal Speakers	15W (x1)
Audible Noise (Normal)	32dB
Audible Noise (Eco)	27dB
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	165W
Stand-by	<0.5W
Physical Controls	Keypad, Power key
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104º F (0 - 40º C)
Kensington Lock Slot	1
Net (lbs)	6.4
Gross (lbs)	10.14
Net (kg)	2.9
Gross (kg)	4.6
Packaging (in.)	15.75 x 11.02 x 6.10
Physical (in.)	11.26 x 8.50 x 5.08
Packaging (mm)	400 x 280 x 155
Physical (mm)	286 x 216 x 129
Regulations	cTUVus, CE, FCC, RoHS, REACH, EEE
Package Contents	Projector, power cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907038194







Contact Sales

ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com