2 Port Industrial Wall Mountable USB to Serial Adapter Hub with DIN Rail Clips - TAA

Product ID: ICUSB2322I



The ICUSB2322I 2-Port Industrial USB to Serial Hub with DIN Rail Clips converts a single USB port into two RS232 serial ports, enabling you to connect to, monitor and control your serial devices.

Featuring rugged metal construction, with sturdy wall-mounting brackets and top-hat DIN Rail clips (included), this USB to Serial Hub provides versatile mounting options and a robust solution for both harsh industrial environments and simple desktop installations.

This USB powered adapter also retains assigned serial COM port values once connected, allowing the same values to be automatically reassigned to the ports provided by the adapter.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility





Applications

• Perfect for IT Administrators looking to add legacy functionality to newer notebooks, PCs and servers that lack an integrated RS232 port

• Connect, monitor and control industrial/automotive sensors and equipment

• Connect bar code scanners, receipt printers and other point of sale devices

• Connect a satellite receiver, serial modem, or PDA with serial sync

• Connect and program LED and Digital signage boards with serial communication ports

Features

• 2-port USB to RS232 serial adapter

• Rugged metal construction

• Wall-mountable, with included DIN Rail clips

• COM retention: COM Port assignments maintained across reboot

• Baud Rate up to 921.6 Kbps

General		
	UPC	065030846943
	Package Quantity	1
	Warranty	2 Years
Power		
	Power Source	USB-Powered
	Input Voltage	5V DC
	Output Voltage	5 DC
	Plug Type	M
Physical & Environmental		

	Color	Black
	Material	Steel
	Cable Length	6.0 ft [1.8 m]
	Product Length	4.1 in [10.4 cm]
	Product Width	2.6 in [66 mm]
	Product Height	0.9 in [24 mm]
	Weight of Product	5.7 oz [162 g]
	Operating Temperature	0C to 55C (32F to 131F)
	Storage Temperature	-20C to 85C (-4F to 185F)
	Humidity	5~95% RH
Performance		
	Data Bits	7, 8
	FIFO	256 Bytes
	Parity	Odd, Even, Mark, Space, None
	Stop Bits	1, 2
	Max Baud Rate	921.6 Kbps
	Serial Protocol	RS-232
Hardware		
	Number of Ports	2
	Interface	Serial
	Bus Type	USB 2.0
	Port Style	External Hub
	Chipset ID	FTDI - FT232RL
	LED Indicators	2 - Each, Tx/Rx Activity indicators
Packaging & In-the-Box		
	Included in Package	1 - USB to RS-232 Serial Adapter

		1 - DIN rail kit
		1 - 6 ft USB A to B cable
		1 - Instruction Manual
	Package Width	8.2 in [20.8 cm]
	Package Depth	5.7 in [14.5 cm]
	Package Height	1.7 in [43 mm]
	Shipping (Package) Weight	12.4 oz [352 g]

Connector(s)		
	Connector 1 (Quantity)	1
	Connector 1	USB-B (480Mbps, 2.5W)
	Connector 2 (Quantity)	2
	Connector 2	DB-9 Serial

Product appearance and specifications are subject to change without notice.