2 Port USB VGA Cable KVM Switch - USB Powered with Remote Switch

Product ID: SV211USB



The SV211USB 2-Port VGA Cable KVM Switch lets you control two VGA, USB-equipped PCs with a single monitor, keyboard and mouse.

To help organize your desk without sacrificing valuable work space, this VGA USB KVM switch features a compact footprint and integrated KVM cables that can be connected directly to your systems. Plus, the KVM is USB-powered, eliminating the need for a bulky external power adapter and wall outlet.

This VGA KVM switch offers support for resolutions up to 2048x1536, for the ability to drive a high-resolution VGA display. For simple switching between connected systems, the KVM features a convenient push-button remote switch on a 1.5 meter (5ft) cable, as well as keyboard hot-key support and PC or Mac compatible switching software.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

• Great for PC test/burn-in computer control, saving the desk space required for two monitors, keyboards and mice

• Perfect for sharing computers and attached peripherals in the home or home office

• Dual system control for single user workstations, increasing user productivity in the office

Features

• Supports resolutions up to 2048x1536

• Switch PCs via push-button, hot-keys or switching software (included)

• Space-saving design, minimal footprint

• Integrated KVM cables and remote switch

• Switching software supports PC and Mac platforms

General		
	UPC	065030858625
	Package Quantity	1
	Warranty	2 Years
Special Notes / Requirements		
	Special Notes	OS Compatibility refers to KVM software only - the KVM itself can be used without software on any platform
Power		
	Power Source	USB-Powered
	Input Voltage	5V DC
	Output Voltage	5 DC
Physical & Environmental		
	Color	Black
	Material	Plastic
	Cable Length	33.5 in [85 cm]
	Product Length	3.5 in [88 mm]
	Product Width	2.6 in [66 mm]
	Product Height	0.9 in [23 mm]

	Weight of Product	11.3 oz [321 g]
	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-20C to 60C (4F to 140F)
	Humidity	0~90% RH Non-Condensing
Performance		
	IP Control	No
	Hot-Key Selection	Yes
	Port Selection Support	Push Button, Hotkeys, and Software
	On-Screen Display	No
Hardware		
	CAC Support	No
	Audio	No
	Number of KVM Ports	2
	Supported Platforms	USB
	PC Video Type	VGA
	Number of Monitors Supported	1
	Rack-Mountable	No
	Cables Included	Yes
	Cascadable	No
	LED Indicators	1 - PC Selection indictor
Packaging & In-the-Box		
	Included in Package	1 - KVM Switch
		1 - Software CD
		1 - Instruction Manual
	Package Width	9.8 in [24.9 cm]

	Package Depth	6.4 in [16.2 cm]
	Package Height	2.5 in [64 mm]
	Shipping (Package) Weight	14.2 oz [402 g]

Connector(s)		
	Host Connector 1 (Quantity)	1
	Host Connector 1	VGA
	Host Connector 2 (Quantity)	1
	Host Connector 2	USB-A (480Mbps, 2.5W)
	Connector 1 (Quantity)	1
	Connector 1	VGA
	Connector 2 (Quantity)	2
	Connector 2	USB-A (480Mbps, 2.5W)

Product appearance and specifications are subject to change without notice.