USB-C Multiport Adapter with HDMI - USB 3.0 Port - 60W PD - White

**Product ID:** CDP2HDUACPW




This USB-C multiport adapter with HDMI lets you add vital connections to your MacBook or Windows laptop, through a single USB-C port.

For maximum productivity, connect your USB-C or Thunderbolt 3 laptop to a 4K 30Hz monitor, using this USB-C to 4K HDMI adapter. You can also connect to an HDMI projector or TV in a boardroom or other meeting space, to deliver presentations on a shared screen.

The USB-C adapter lets you power and charge your USB-C laptop during a presentation or while you're working, with a USB-C Power Delivery port. Even if your laptop has only a single USB-C port available, you can keep your laptop powered.

This USB-C multiport adapter offers a USB 3.0 port that's backward compatible with older USB devices - ideal for data transfers, syncing, or charging your mobile devices.

The compact all-in-one adapter is a vital accessory for your USB-C laptop. With its small-footprint design, you can take it with you anywhere you would use your laptop.

CDP2HDUACPW is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Note: To ensure full adapter functionality, your laptop's USB-C port must support USB Power Delivery and DP Alt Mode.

## Certifications, Reports and Compatibility

Operating System Independent

## Applications

• Multitask faster with an additional, 4K HDMI monitor

• Deliver presentations from your laptop on an HDMI TV or projector

• Charge your laptop with your laptop’s USB-C charger, even while the adapter is connected

## Features

• CONNECT TO 4K HDMI: This white USB C multiport adapter with HDMI lets you connect your USB-C laptop to a 4K UHD HDMI external monitor (4096 x 2160 resolution at 24Hz or 3840 x 2160 @ 30Hz). It's the ideal accessory for a MacBook or other USB-C laptop

• POWER AND CHARGE: The USB-C adapter with charging supports Power Delivery 2.0 (up to 60W), so you can use your laptop's USB-C power adapter to power and charge your laptop

• CONNECT A USB DEVICE: The all-in-one adapter lets you connect a peripheral device like a flash drive or mouse using the USB 3.0 (Type A) port. The USB ports is backward compatible so you can still connect your existing USB device

• TRAVEL-FRIENDLY DESIGN: The compact design lets you carry the portable USB C HDMI multiport adapter with you wherever you go

• THE IT PRO'S CHOICE: Designed and built for IT Professionals, this USB Type C multiport adapter is backed for 3 Years, including free lifetime 24/5 multi-lingual technical assistance

| | | |
|---|---|---|
| **General** | | |
| | UPC | 065030867160 |
| | Package Quantity | 1 |
| | Warranty | 3 Years |
| **Special Notes / Requirements** | | |
| | Special Notes | Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports USB Power Delivery 2.0 and DP alt mode.<br><br>The adapter can connect to a host laptop’s USB-C port that doesn’t support USB Power Delivery 2.0. However, in this configuration if a power adapter is connected to the multifunction adapter, it will not pass power through to your host laptop.<br><br>A 4K-capable display is required to achieve 3840 x 2160p |

| | | |
|---|---|---|
| | | resolution (4K is also known as 4K x 2K) |
| | | USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps. |
| | System and Cable Requirements | A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support USB Power Delivery 2.0 and DP alt mode). |
| | | Optional: USB-C power adapter (for example, your laptop's USB-C based power adapter). |
| **Power** | | |
| | Power Source | USB-Powered |
| | Power Delivery | 60W |
| **Physical & Environmental** | | |
| | Color | White |
| | Material | Plastic |
| | Cable Length | 3.9 in [100 mm] |
| | Product Length | 2.4 in [60 mm] |
| | Product Width | 2.0 in [50 mm] |
| | Product Height | 0.4 in [11 mm] |
| | Weight of Product | 1.3 oz [36 g] |
| | Operating Temperature | 0C to 40C (32F to 104F) |
| | Storage Temperature | -20C to 70C (-4F to 158F) |
| | Humidity | 0~90% RH (Non-condensing) |
| **Performance** | | |
| | Maximum Data Transfer Rate | 5 Gbps (USB 3.0) |
| | Type and Rate | USB 3.0 (5Gbps) |
| | UASP Support | Yes |
| | Maximum Digital Resolutions | 4096 x 2160p @ 24Hz / 3840 x 2160p @ 30Hz<br>Lower resolutions are also supported. |

| | | |
|---|---|---|
| **Hardware** | | |
| | Fast-Charge Port(s) | No |
| | 4K Support | Yes |
| | Displays Supported | 1 |
| | Number of Displays | 1 |
| | Industry Standards | USB 3.0 - Backward compatible with USB 2.0 and 1.1 |
| | Chipset ID | VIA/VLI - VL100 |
| | | VIA/VLI - VL210 |
| | | Parade - PS176 |
| **Packaging & In-the-Box** | | |
| | Included in Package | 1 - USB-C to 4K HDMI multifunction adapter |
| | Package Width | 5.7 in [14.4 cm] |
| | Package Depth | 6.9 in [17.5 cm] |
| | Package Height | 1.3 in [33 mm] |
| | Shipping (Package) Weight | 4.5 oz [128 g] |
| **Connector(s)** | | |
| | Connector 1 (Quantity) | 1 |
| | Connector 1 | USB-C (5Gbps, 4.5W) |
| | Connector 2 (Quantity) | 1 |
| | Connector 2 | USB-C (100W PD Only) |
| | Connector 3 (Quantity) | 1 |
| | Connector 3 | HDMI |
| | Connector 4 (Quantity) | 1 |
| | Connector 4 | USB-A (5Gbps, 4.5W) |

***Product appearance and specifications are subject to change without notice.***