USB VGA KVM Console Extender over CAT5 UTP (500 ft) - TAA

Product ID: SV565UTPUEU



The SV565UTPUEU USB VGA KVM Console Extender over CAT5 UTP (500 ft) lets you control a server, computer or multiple computers (connected through KVM Switch) over a standard Cat5 or Cat6 UTP network cable connection, at distances of up to 500 ft (150 m) away. PC connection cables are included with this product for a ready out of the box solution.

You can use your existing keyboard, mouse, and monitor to access both the server room and your office computer, saving space and avoiding the need for a dedicated remote console by allowing you to switch between workstation view and KVM view at the remote location.

This product is TAA compliant and backed by a Startech.com 2-year warranty with free lifetime technical support.

Certifications, Reports and Compatibility

Applications

• Monitor computer-controlled equipment in a factory or warehouse

• Use one or more servers in a server room from a remote location

• Control remote machines and security monitoring systems

Features

• Can be used with a single computer or connected to an existing KVM switch

• Easy installation using industry standard UTP network cable

• Cables Included for a ready out of the box setup

• Intuitive hot-key commands

• Supports auto-switching between host and remote users or dedicated control

General		
	UPC	065030834506
	Package Quantity	1
	Warranty	2 Years
Special Notes / Requirements		
	Special Notes	Product weights/measurements indicate a single unit only (either Host or Remote)
Power		
	Power Source	AC Adapter Included
	Input Voltage	100 - 240 AC
	Input Current	0.2A
	Output Voltage	9V DC
	Output Current	0.6 A
	Center Tip Polarity	Positive
	Plug Type	M
	Power Consumption	5.4
Physical & Environmental		
	Color	Black
	Material	Steel

	Product Length	3.0 in [75.0 mm]
	Product Width	6.1 in [15.5 cm]
	Product Height	0.8 in [20.0 mm]
	Weight of Product	10.6 oz [299.0 g]
	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-20C to 60C (-4F to 140F)
	Humidity	0~80% RH
Performance		
	Max Transfer Distance	150m [492ft]
	IP Control	No
	MTBF	126000 hours
	Supported Resolutions	1280 x 1024 @ 300ft/ 100m
		1024 x 768 @ maximum cable length
Hardware		
	Audio	No
	Number of KVM Ports	2
	Supported Platforms	USB
	PC Video Type	VGA
	Number of Monitors Supported	1
	Rack-Mountable	No
Packaging & In-the-Box		
	Included in Package	1 - Host Unit
		1 - Remote Unit
		2 - 6 ft 2-in-1 USB VGA KVM cables
		2 - Packs Rubber Feet
		1 - Power Adapter

		1 - Manual
	Package Width	11.8 in [29.9 cm]
	Package Depth	10.0 in [25.3 cm]
	Package Height	3.4 in [86 mm]
	Shipping (Package) Weight	3.4 lb [1.5 kg]
Connector(s)		
	Host Connector 1 (Quantity)	2
	Host Connector 1	VGA
	Connector 1 (Quantity)	2
	Connector 1	RJ-45
	Connector 2 (Quantity)	2
	Connector 2	VGA
	Connector 3 (Quantity)	4
	Connector 3	USB-A (480Mbps, 2.5W)

Product appearance and specifications are subject to change without notice.