Product Code:

7832

4-TAKT POWERBIKE

Synthetic 4-stoke Engine Oil

Meets the requirements:

SAE 15W-50, API SN, JASO MA/MA2, DUCATI, HONDA, KAWASAKI, SUZUKI, YAMAHA

An innovative synthetic ester-containing engine oil for 4-stroke high-load engines of motorcycles, pit bikes, motards, etc. for off-road (enduro, motocross, trials, etc.) and highway (stuntriding, supermoto, etc.) driving under extreme loads. It was designed for a guaranteed protection of the engine and the durability of the gearbox.



Product Characteristics:

Test	Method	Unit	Result
Dynamic vicosity at 20 °C	D 5293	[cP](mPas)	7002
Density at 15 °C	D 1298	kg/m³	890
Viscosity at 40 °C	D 445	CSt	157,72
Viscosity at 100 °C	D 445	CSt	17,66
Viscosity index	D 2270		123
Flash point	D 92	°C	224
TBN	D 2896	mgKOH/g	8,15
Pour point	D 97	°C	-27
Ignition temperature			350
Mechanical impurities	D 2273	%	-

Volume:

1L	MN7832-1	60L	MN7832-60
4Lmet.	MN7832-4ME	208L	MN7832-DR
10L	MN7832-10	1000L	MN7832-IBC

www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®