Product Code:

7812

4-TAKT MOTORBIKE

Synthetic 4-stroke Engine Oil



An innovative synthetic ester-containing engine oil for 4-stroke high-load engines of motorcycles, pit bikes, motards, etc. for off-road (enduro, motocross, trials, etc.) and highway (stuntriding, supermoto, etc.) driving under extreme loads. It was designed for a guaranteed protection of the engine and the durability of the gearbox.

Meets the requirements:

SAE 10W-40, API SL, JASO MA/MA2, HONDA, HUSABERG, KAWASAKI, SUZUKI, YAMAHA

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m³	870
Viscosity at 40°C	D 445	CSt	90,88
Viscosity at 100°C	D 445	CSt	13,64
Viscosity index	D 2270		152
Flash point	D 92	°C	222
Total base, mgKOH/g	D 2896		6,22
Pour point	D 97	°C	-38
Dynamic viscosity at -25°C	D 5293	°C	6049
High-shear-rate viscosity at 150°C	D 4741	°C	3,60

Volume:

1L	MN7812-1	10L	MN7812-10
1Lmet	MN7812-1 ME	60L	MN7812-60
4L	MN7812-4	208L	MN7812-DR
4Lmet	MN7812-4 ME	1000L	MN7812-IBC

www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®