Product Code:

8101

FWD GETRIEBEOEL

Semi-synthetic Gear Oil

A latest-generation energy-conserving all-season semi-synthetic gear oil for manual transmissions. It is recommended for use in all types of synchronized manual transmissions (including transmissions with an incorporated differential in front wheel drive vehicles) and in heavy-duty non-synchronized manual transmissions, transfer cases and main gears, in which the application of the standard GL-4 and/or MT-1 is prescribed.



Meets the requirements:

SAE 75W-85, API GL-4, API MT-1, MIL L 2105

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m³	890
Viscosity at 40°C	D 445	CSt	62,88
Viscosity at 100°C	D 445	CSt	77,35
Viscosity index	D 2270		176
Flash point	D 92	°C	210
Pour point	D 97	°C	-46
Brookfield dynamic viscosity at -40°C max	D 2983	°C	148 000

Volume:

1L	MN8101-1	60L	MN8101-60
4L	MN8101-4	208L	MN8101-DR
10L	MN8101-10	1000L	MN8101-IBC
20L	MN8101-20		

www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®