Product Code:

7814

4-TAKT MOTORBIKE

Synthetic 4-stroke Engine Oil

Meets the requirements:

SAE 10W-50, API SN, JASO MA/MA2, HONDA, HUSABERG, KAWASAKI, SUZUKI, YAMAHA

An innovative synthetic ester-containing engine oil for 4-stroke high-load engines of motorcycles, pit bikes, motards, etc. for off-road (enduro, motocross, trials, etc.) and highway (stuntriding, supermoto, etc.) driving under extreme loads. It was designed for a guaranteed protection of the engine and the durability of the gearbox.



Product Characteristics:

Test	Method	Unit	Result
Color	visual		RED
Dynamic vicosity at -25 °C	D 5293	[cP](mPas)	6718
Density at 15 °C	D 1298	kg/m³	859
Viscosity at 40 °C	D 445	CSt	116.0
Viscosity at 100 °C	D 445	CSt	16.70
Viscosity index	D 2270		154
Flash point	D 92	°C	224
Total base no.	D 2896	mgKOH/g	8.81
Pour point	D 97	°C	-38
Ignition temperature			350
Mechanical impurities	D 2273	%	-

1L	MN7814-1
4L	MN7814-4

www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®