

UT107

Automotive Multi-Purpose Meters



[Enlarge](#)



[Download Manual](#)

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/1000V	±(0.5%+2)
AC Voltage	200V/750V	±(0.8%+5)
DC Current	200mA/10A	±(0.8%+5)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/20MΩ	±(0.8%+5)
Temperature (°C)	-40°C~1000°C	±(2%+8)
Frequency	2kHz	±(2%+5)
Duty Cycle	1%~90%	±(4%+5)
Special Functions		
Fused 10A Range		✓
Battery Test	12V	±(3%+5)
Dwell	4Cyl/6Cyl/8Cyl	±(3%+5)
Tach	4Cyl/6Cyl/8Cyl	±(3%+5)
Diode		✓
Continuity Buzzer		✓
Data Hold		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	✓
Max. Display	1999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	60 x 54mm
Product Colour	Red Meter and Grey Holster
Product Net Weight	352g (Including Holster)
Product Size	179 x 88 x 39mm
Standard Accessories	Test Lead, Battery, English Manual, Holster, Point Contact Temperature Probe
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40pcs
Standard Carton Measurement	598 x 418 x 340mm (0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	22kg

Specifications and other information are subject to change without further notice.

[Back to main menu](#)