

# LÍNEA ALUMBRADO PÚBLICO MINI CROSS



APMC50WF



APMC60WF



APMC70WF



APMC100WF



APMC135WF



APMC150WF



APMC200WF

## CARACTERÍSTICAS

SKU	MODELO	POTENCIA	MATERIAL	COLOR T°	CRI	EFICIENCIA LUMÍNICA	FIJACIÓN	DIMENSIONES (MM)
APMC50WF	Mini Cross	50W	Aluminio	6500K	≥70	130 Lm/W	Universal	530 (L) 370 (An) 95 (Al)
APMC60WF	Mini Cross	60W	Aluminio	6500K	≥70	130 Lm/W	Universal	530 (L) 370 (An) 95 (Al)
APMC70WF	Mini Cross	70W	Aluminio	6500K	≥70	130 Lm/W	Universal	600 (L) 370 (An) 95 (Al)
APMC100WF	Mini Cross	100W	Aluminio	6500K	≥70	130 Lm/W	Universal	600 (L) 370 (An) 95 (Al)
APMC135WF	Mini Cross	135W	Aluminio	6500K	≥70	130 Lm/W	Universal	710 (L) 370 (An) 95 (Al)
APMC150WF	Mini Cross	150W	Aluminio	6500K	≥70	130 Lm/W	Universal	710 (L) 370 (An) 95 (Al)
APMC200WF	Mini Cross	200W	Aluminio	6500K	≥70	130 Lm/W	Universal	808 (L) 370 (An) 95 (Al)



DRIVER  
MEAN WELL



TECNOLOGÍA  
LED CREE



PROTECCIÓN  
IP66 - IK08 - Clase I



VOLTAJE  
AC100-277V 50-60HZ



MONTAJE  
6 MT. A 15 MT.



FIJACIÓN UNIVERSAL  
BRAZO POSTE /  
PARTE ALTA POSTE

PF FACTOR POTENCIA  
0,97



✉ claudio@elights.cl 📞 +56950039803 📷 📘 🐦 🌐

