TriBrer®

TB-700

Multi-Functions Testing Platform

FITX Test Solutions

CE

ISO 9001 CAS

IAF

ISO14001:2015

ISO 45001

SPECIFICATION

Wavelength	1310/1550nm
Dynamic range	22/20dB
Distance setting	Max. 80km
Connector	FC/UPC interchangeable adapter or customize
Pulse width	5ns~20μs
Event dead zone	1m
Attenuation dead zone	7m
OLS function	Same wavelength and connector as OTDR
OPM function	+26~-50dBm, 850/1300/1310/1490/1550/1625nm, 2.5mm UPP
VFL function	10mW, 2.5mm universal connector
Storage	Internal memory or TF card(optional)
Power & Data port	TYPE-C
Power bank	Type-A 3.7V, 5000mAh
Operation Temperature	0~+50℃,<90% RH
Storage Temperature	-20~+70℃,<90% RH
Size	160*85*38mm
Weight	About 430g

ACCESSORIES

STANDARD

Carrying Bag

CD

Manual

Calibration Certificate

Packing Box

AC/DC Adapter
Type -C

OPTIONAL

FCU=FC/UPC
FCA=FC/APC

SCU=SC/UPC
SCA=SC/APC

LCU=LC/UPC

STU=ST/UPC

ORDERING INFORMATION

TB-700-FCU, OTDR FC/UPC connector

TB-700-SCU, OTDR SC/UPC connector

TB-700-SCA, OTDR SC/APC connector

Copyright © 2020, Zhejiang TriBrer Communication LTD
Copyright © 2020, Zhejiang TriBrer Communication LTD