F



IP44

PAINEL

LED DE ENCASTRAR

PAINEL LED EMPORTABLE - RECESSED LED PANEL

PT) Descrição do produto

Painel LED de encastrar 3CCT com furo ajustável, fabricado em alumínio e PC. O seu índice de proteção IP44 permite que seja instalado em zonas sujeitas a alguma humidade e poeira. A cor de luz pode ser ajustada entre 3000K, 4000K e 6000K.

ES) Descripción del producto

Panel LED empotrable 3CCT con orificio ajustable, fabricado en aluminio y PC. Su grado de protección IP44 permite su instalación en zonas sometidas a cierta humedad y polvo. El color de la luz puede ajustarse entre 3000K, 4000K y 6000K.

EN) Product description

3CCT recessed LED panel with adjustable hole, made of aluminum and PC. Its IP44 protection rating allows it to be installed in areas subject to some humidity and dust. The light color can be adjusted between 3000K, 4000K and 6000K.







Características Gerais - Características generales - General Features

Temperatura de Trabalho - Temperatura de funcionamiento - Working Temperature
-20 ~ 40°C

Frequência de Operação - Frecuencia de funcionamiento - Operating Frequency
50-60Hz

Voltagem - Tensión - Voltage
AC 85-265V

Potência - Potencia - Power
18W

Lumens
1440lm

Cor de Luz - Color de la Luz - Light Color
3CCT - 3000K/4000K/6000K

Tempo Útil de Vida - Vida Útil - Lifetime
25.000h

Ângulo do Feixe - Ángulo del rayo - Beam Angle
120°

Acabamento - Acabado - Finishing
Branco - Blanco - White

Material
Alumínio e PC - Aluminio y PC - Aluminum and PC

IP	CRI	LED
44	≥80	SMD

Desenho Técnico - Dibujo Técnico - Technical Drawing



SKU

39212