



(Charging cups pictured not included with KMB-28 Power Source)

KMB-28

MULTIPLE POWER SOURCE INSTRUCTION MANUAL

The KMB-28 is a power source for chargers, and is a compact steel rack unit which can hold up to six KENWOOD desk-top chargers, model KSC-35. The KMB-28 is a UL listed I.T.E. power source, is certified to UL and CSA safety standards, and is provided with a three-wire grounded power cord for 120V AC operation. The KMB-28 is intended for desktop or shelf mounted installation, in weather-protected, dry locations (indoors only). Optionally; 2 units may be fastened side by side using supplied hardware.

BEFORE APPLYING POWER

IMPORTANT! This unit is designed for 120V AC operation, only.

CONNECTION: Connect the AC plug to an unswitched 120V AC power source only after all chargers are installed in the adapter and the charger locking bar is secured.

SPECIFICATIONS

Use:	Holds up to six KSC-35.
Dimensions:	10 9/16" W x 2 3/8" H x 9 1/2" D inches
Finish	Black powder coat
Material	18 Gauge CRS (Cold Rolled Steel)
Weight, loaded	8 lbs. (3.6kg) with chargers & radios
Temperature Range	10 to 35° C (50 to 95° F) Operating (Charging)
Power Requirement	120V AC, 60 Hz, 90W max.
Safety Approvals:	UL and CSA Information Technology safety standards
Protection:	Internal fuse, not user accessible
Power Cord length	7 1/2'. AC Line Cord

NOTE: Ratings are subject to change without notice or obligation due to advancements in technology.

