UL INFORMATION



Versions of the IC-F52D-UL, IC-F62D-UL which display the "UL LISTED" marking on the seal.

Intrinsically safe:	Class I, Division 1, Groups C D; Class II, Division 1, Groups E F G; Class III. T3C.
Non-incendive:	Class I, Division 2, Groups A B C D.
Ambient temperature:	–20°C (–4°F) ~ +60°C (+140°F)
Standards of safety:	ANSI/TIA-4950-A ANSI/UL 121201

Intrinsically Safe when used with Icom BP-292UL battery pack.

⚠ **WARNING!** Risk of fire, explosion, and burns. Do not disassemble, crush, heat above 100°C (212°F) or Incinerate.

⚠ **WARNING!** Substitution of Components may impair intrinsic safety.

CAUTION: DO NOT change batteries or accessories in a hazardous area.
When the transceiver is used in a hazardous area, the BP-292UL **MUST** be attached, either the jack cover or HM-184UL **MUST** be attached to the speaker-microphone connector.

◇ For the battery pack

⚠ **WARNING! NEVER** charge the BP-292UL (with/without the transceiver) in an explosive atmosphere.

⚠ **WARNING!** Batteries must only be changed or charged in an area known to be non-hazardous, non-classified safe location.

⚠ **WARNING!** The battery may present a risk of fire or chemical burn if mistreated. Do not disassemble, heat above 100°C (212°F), or incinerate. Follow manufacturer's instructions.

CAUTION: DO NOT charge the battery outside of the specified temperature range: 10˚C ~ 45˚C (50˚F ~ 113˚F).

Dispose of used battery promptly. Keep away from children.

Do not disassemble and do not dispose of in fire.

Replace Li-ion battery pack Model Number BP-292UL manufactured by Icom Inc. only. Use of another battery may present a risk of fire or explosion.

DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE MAY BE PRESENT.