RAVENOL Hydraulik PSF Fluid

Kategorie: Car hydraulic oil

Artikelnummer: 1181000

Oil type: Synthetic

Recommendation: Citroën/Peugeot 9735EJ für C-Crosser, Peugeot 4007, Honda PSF-S, Hyundai PSF-3, KIA PSF-III, Mazda PSF, Mitsubishi Diamond PSF-2M, Peugeot 4007, Subaru PS Fluid, Toyota PSF-EH

Application: Passenger car



1L | 1181000-001
4L | 1181000-004
10L | 1181000-010
20L | 1181000-020
20L | 1181000-B20
60L | 1181000-060
208L | 1181000-208
1000L | 1181000-700

RAVENOL Hydraulik PSF Fluid is a specific synthetic hydraulic fluid for power steering.

RAVENOL Hydraulik PSF Fluid is guaranteeing an optimized power transmission.

RAVENOL Hydraulik PSF Fluid is produced on the basis of high quality base oils with special additives and inhibition which guarantees a perfect function of the hydraulics.

Application Note

RAVENOL Hydraulik PSF Fluid is especially developed for the use as a hydraulic fluid in power transmissions.

Characteristics

- A very low pour point
- An excellent foam prevention, no foam formation
- A good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- A very good oxidation stability
- Excellent protection against wear and tear, corrosion and foam formation
- Fine tuned coefficient of friction
- eutral behaviour against sealing materials
- Neutral behaviour because of inhibition against non ferrous metals

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	847,0	EN ISO 12185
Colour		rot	VISUELL
Viscosity at 100 °C	mm²/s	7,2	DIN 51562-1
Viscosity at 40 °C	mm²/s	34,8	DIN 51562-1
Viscosity Index VI		178	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	12800	ASTM D2983
Pourpoint	°C	-48	DIN ISO 3016
Flashpoint	°C	211	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

29.05.2023