



SCANNER ONE 8 Ray

Especificaciones:

| | | | |
|------------------------|---|---------------------|------------------------------|
| Light Source | Visible Laser Diode 650mm | Size | L x W x H:170mm x 71mm |
| Scan Pattern | Single Scan & Manual | Charge Mode | Wired Charging |
| Working Frequency | 433 MHz frequency | Weight | 180g |
| Communication Distance | Up to 300m at open places | Material | ABS+PC |
| Scan Precision | 3mil | Voltage | 2200 mAh/DC 5V |
| Scan Rate | 300 times/second | Operating Current | 110mA/35mA |
| Scan Width | 30mm@scan window, 220mm@200m | EMC | CE & FCC DOC compliance |
| Depth of Scan Field | 0-280mm(0.33mm pcs0.9) | IP Standard | IP54 |
| Scan Angle | 30° & 65° & 55° | Decoding Capability | all 1D barcode Including GS1 |
| Communication Distance | 300m | Humidity | 5% to 95% relative humidity |
| Print Contrast | 10% UPC/EAN 100% | Shock | 1.5M drops |
| Interface | USB | | |
| Decoding Capability | UPC-A; UPC-E; EAN-8; EAN-13; Code39; Codabar; Code128; Interleaved 2 of 5; Industrial 2 of 5; Matrix 2 of 5; Code 93; UCC/EAN 128; MSI; UK/Plessey; ISBN/ISSN; GS1 Databar Expanded; GS1 Databar; GS1 Databar Limited, etc. | | |