REIGN E+ 3

ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
MANDO	RideControl GO integrated in TT, RideControl Ergo 3
PANTALLA	Wireless display compatible
BATERÍA	EnergyPak Smart 800,EnergyPak Plus range extender compatible (exclude S Size)
CUADRO	
TALLAS	S, M, L, XL
COLORES	Cobalt/Black
CUADRO	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, patilla de cambio UDH
HORQUILLA	RockShox Domain R 29er, 170mm travel, 15x110 Boost, Maxle Stealth, E-bike Approved
AMORTIGUADOR	Fox Float DPS Performance, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned
COMPONENTES	
MANILLAR	Giant Contact Trail, 35x800mm
PUÑOS	Giant Tactal Pro-E, single lock-on
POTENCIA	Giant Contact SL 35
TIJA DE SILLÍN	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SILLÍN	Giant Romero Trail
PEDALES	Flat pedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore
DESVIADOR	MRP 1X HD2 custom co-molded chain guide
CAMBIO TRASERO	Shimano Deore 12-speed
FRENOS	Shimano Deore BR-M420, 4-piston, hydraulic disc, 203mm
PALANCAS DE FRENOS	Shimano Deore, I-spec EV
CASETTE	Shimano Deore CS-M6100-12, 10-51T, 12-speed
CADENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
JGO. PLATOS Y BIELAS	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S/M:160, L/XL:165)
CAJA DE PEDALIER	n/a

RUEDAS	
LLANTAS	Giant AM 29" [F] 27.5"[R], Tubeless ready, 30mm inner width
BUJES	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RADIOS	Sapim E-Lite [R] Race [F], e-bike optimized
CUBIERTAS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F]Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESORIOS	
LUCES	-
CANDADO/ANTI-ROBO	Torx 25 Battery Lock with built-in Torque limiter
PORTA-EQUIPAJES	-

Precio: 5.499,00 €

GEOMETRÍA

CUADRO	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Longitud del tubo del sillín (mm)	400	425	450	475
Ángulo del tubo del sillín	76,7° | 77,5°	76,7° | 77,5°	76,7° | 77,5°	76,7° | 77,5°
Longitud del tubo superior (mm) (mm)	569 | 568	595 | 594	622 | 621	649 | 648
Longitud del tubo de dirección (mm) (mm)	100	100	110	120
Ángulo del tubo de dirección	63,7° | 64,5°	63,7° | 64,5°	63,7° | 64,5°	63,7° | 64,5°
Inclinación de la horquilla (mm)	44	44	44	44
Trail (mm) (mm)	135,5 | 132,1	135 | 132	135 | 132	135,5 | 132,1
Distancia entre ejes (mm) (mm)	1209 | 1210	1236 | 1237	1265 | 1266	1295 | 1296
Longitud de la vaina (mm) (mm)	457 | 455	454 | 454	454 | 454	454 | 454
Caída del eje de pedalier (mm) (mm)	25 | 15	25 | 15	25 | 15	25 | 15
Stack (mm) (mm)	636 | 632	635 | 632	645 | 641	654 | 650
Reach (mm) (mm)	425 | 430	450 | 455	475 | 480	500 | 505
Altura del suelo al tubo (mm) (mm)	785 | 789	772 | 776	771 | 775	768 | 772
Ancho del manillar (mm) (mm)	800	800	800	800
Longitud de la potencia (mm) (mm)	40	40	50	50
Longitud de las bielas (mm) (mm)	160	160	165	165
Tamaño de ruedas	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]	29" [F] 27.5" [R]

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.