REIGN E+ 3

ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
MANDO	Giant RideControl Ergo3, grip integrated remote
PANTALLA	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATERÍA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible (exculde S size)
CARGADOR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	S, M, L, XL
COLORES	Raw Aluminum / Black
CUADRO	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Derailleur Hanger
HORQUILLA	SR Suntour Durolux 38 Boost EQ, 170mm travel, 44mm offset, RC2, 15LH-110
AMORTIGUADOR	Fox Float Performance, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTES	
MANILLAR	Giant Contact Trail, 35x800mm
PUÑOS	Giant Tactal Pro-E, tapered design, 135mm Ø28~30mm (S/M) 142mm Ø29~32mm (L/XL)
POTENCIA	Giant Contact SL 35
TIJA DE SILLÍN	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/L:170/XL:200)
SILLÍN	Giant Romero Trail
PEDALES	Flatpedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Cues LinkGlide
DESVIADOR	MRP 1X HD2 custom co-molded chain guide
CAMBIO TRASERO	Shimano Cues LinkGlide 11-speed
FRENOS	Shimano BR-MT420, 4-piston, hydraulic disc, 203mm
PALANCAS DE FRENOS	Shimano Deore, I-spec EV
CASETTE	Shimano Cues LinkGlide, CS-LG400-11, 11-50T, 11-speed
CADENA	Shimano LinkGlide, CN-LG500
JGO. PLATOS Y BIELAS	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (S/M:160mm, L/XL:165mm)
CAJA DE PEDALIER	n/a

RUEDAS	
LLANTAS	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
BUJES	Shimano MT410, Boost, Center-Lock, [F] 110x15 [R] 148x12mm HG Drive Body Thru-axle
RADIOS	Sapim E-Lite [R] Race [F], e-bike optimized
CUBIERTAS	Maxxis Minion DHF 29x2.6"" foldable, Tubeless, EXO+, 3C MaxxTerra[F] Maxxis High Roller II 27.5x2.5"" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESORIOS	
CANDADO/ANTI-ROBO	Torx 25 Battery Lock with built-in Torque limiter

Precio: 4.999,00 €

GEOMETRÍA

CUADRO	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Longitud del tubo del sillín (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	230	260	280	310
Ángulo del tubo del sillín	76,7° | 77,5°	76,7° | 77,5°	76,7° | 77,5°	76,7° | 77,5°
Longitud del tubo superior (mm) (mm)	569 | 568	595 | 594	622 | 621	649 | 648
Longitud del tubo de dirección (mm) (mm)	100	100	110	120
Ángulo del tubo de dirección	63,7° | 64,5°	63,7° | 64,5°	63,7° | 64,5°	63,7° | 64,5°
Inclinación de la horquilla (mm)	44	44	44	44
Trail (mm) (mm)	135,5 | 132,1	135 | 132	135 | 132	135,5 | 132,1
Distancia entre ejes (mm) (mm)	1209 | 1210	1236 | 1237	1265 | 1266	1295 | 1296
Longitud de la vaina (mm) (mm)	457 | 455	454 | 454	454 | 454	454 | 454
Caída del eje de pedalier (mm) (mm)	25 | 15	25 | 15	25 | 15	25 | 15
Stack (mm) (mm)	636 | 632	635 | 632	645 | 641	654 | 650
Reach (mm) (mm)	425 | 430	450 | 455	475 | 480	500 | 505
Altura del suelo al tubo (mm) (mm)	785 | 789	772 | 776	771 | 775	768 | 772
Ancho del manillar (mm) (mm)	800	800	800	800
Longitud de la potencia (mm) (mm)	40	40	40	50
Longitud de las bielas (mm) (mm)	160	160	165	165
Tamaño de ruedas	29"	[F] 29" [R	[F] 29" [R	[F] 29" [R

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.