Product datasheet

RF CLAS GL 35 4 W/824 E27

Vintage 1906 LED | LED lamps, vintage edition



Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires
- Perfect for decorative installations

Product benefits

- Very low energy consumption
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Clear lamps with innovative LED "filament" technology

Product features

- LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Lifetime: up to 15,000 h
- Beam angle: up to 360°
- Energy efficiency class: A++



© 2016, LEDVANCE GmbH. All rights reserved.

Technical data

Electrical data

Rated wattage	4.00 W
Nominal wattage	4.00 W
Nominal voltage	220…240 V
Operating frequency	50…60 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	35 W

Photometrical data

Nominal luminous flux	470 lm
Rated luminous flux	470 lm
Color temperature	2400 K
Color rendering index Ra	≥80
Light color (designation)	Warm White
Standard deviation of color matching	≤6 sdcm

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	168.0 mm
Diameter	124.0 mm
Outer bulb	G125
Length	168.0 mm

Lifespan

© 2016, LEDVANCE GmbH. All rights reserved.

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000
Lumen main.fact.at end of nom.life time	0.70

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Appropriate disposal acc. to WEEE	Yes

Capabilities

Dimmable	No

Certificates & standards

Energy efficiency class	A++
Energy consumption	4 kWh/1000h

Country specific categorizations

ILCOS	DRAG/C-4/824-220/240-E27-124
Order reference	1906LEDGLOBE 4W

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899962071	RF CLAS GL 35 4 W/824 E27	Shipping carton box 4	291 mm x 291 mm x 228 mm	19.31 dm^3	958.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2016, LEDVANCE GmbH. All rights reserved.