



VT-519-S 2W WALL SURFACE EMERGENCY EXIT LIGHT WITH SAMSUNG LED 6000K



FEATURES

- Fitted with high efficiency Samsung LED Chips
- High-performance Ni-Cd batteries made for Longevity & low maintenance
- Low energy consumption only 2 watts
- Viewing distance of 24 meters both sides
- Green light indicator test button
- 3 ways different legends included
- Reliable Emergency backup of 3 hours
- Maintained operation

TECHNICAL INFORMATION

Dimmable:	No
Model:	VT-519-S
Battery Charging Current:	100-140mA
Battery Discharge Current:	200-280mA
Working Time:	>3 Hours
No. Of Led:	16
LED Chip Solution:	12V 60mA
Emergency Operation Time:	>3 Hours
Installation Type:	Surfaced
Battery Type:	Ni-Cd 3.6V, 900mAh
Color Temperature:	6000K
Watts:	2
Lumens:	140
Input Power:	AC:220-240V, 50/60Hz
Unit Color:	2938
Color for Web:	White
Body Type:	PC
Dimension:	380x51x195mm
LED Chip Type:	SMD-Samsung Chip
Energy Saving:	85 Energy
Charging Time:	12 hours
Samsung:	Yes
IP Rating:	IP20

EMC Certificate: [Check the certificate](#)

LVD Certificate: [Check the certificate](#)

ROHS Certificate: [Check the certificate](#)

IP20
STANDARD

03
YEAR
WARRANTY



LISTING DETAILS

SKU:	836
Model:	VT-519-S
EAN:	3800157641357
Commodity Code:	94056120

PACKAGING

Gross Weight (Kgs):	1.1
Unit CBM:	0.003693375
Dimension:	380x51x195mm

MASTER BOX PACKAGING

Box Qty:	10
Qty Per Pallet:	300
Length (Box) mm:	45
Width (Box) mm:	335
Height (Box) mm:	245

