

CorePro LEDluster

Corepro Lustre ND 4-25W E14 827 P45 CL

The frosted CorePro LEDluster is designed for retrofit replacement of incandescent lamps. It is compatible with fixtures with an E27 or E14 holder. LEDlamps deliver huge energy savings and minimize maintenance cost.

Product data

General Information	
Cap base	E14 [E14]
Bulb shape	P45 [P 45mm]
Nominal lifetime (nom.)	15000 h
Switching cycle	50000X
Technical type	4-25W

Light Technical	
Luminous flux (nom.)	250 lm
Luminous flux (rated) (nom.)	250 lm
Colour designation	Warm white (WW)
Correlated colour temperature (nom.)	2700 K
Luminous efficacy (rated) (nom.)	65 lm/W
Colour consistency	<6
Color rendering index (nom.)	80
LLMF at end of nominal lifetime (nom.)	70 %

Operating and Electrical	
Input frequency	50-60 Hz
Power (Rated) (Nom)	4 W
Lamp current (nom.)	35 mA
Wattage equivalent	25 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	instant full light
Power factor (nom.)	0.4
Voltage (Nom)	220-240 V

Temperature	
T-Case maximum (nom.)	85 °C

Controls and Dimming	
Dimmable	no

Mechanical and Housing	
Bulb finish	Clear (CL)

Approval and Application	
Suitable for accent lighting	No
Energy efficiency label (EEL)	A+
Energy Consumption kWh/1000 h	4 kWh


Product Data	
Full product code	871869650759900
Order product name	Corepro Lustre ND 4-25W E14 827 P45 CL
EAN/UPC – product	8718696507599
Order code	50759900

CorePro LEDluster

Numerator – quantity per pack	1
Numerator – packs per outer box	10
Material no. (12NC)	929001142302

Net weight (piece)	0.040 kg

Dimensional drawing



LED ND 4-25W E14 827 220-240V P45 CL

Product	D	C
Corepro Lustre ND 4-25W E14 827 P45 CL	45 mm	88 mm

© 2016 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.