

MASTERColour CDM-R111

MASTERColour CDM-R111 70W/942 GX8.5 40D 1CT/6

The MASTERColour CDM-R111 combines the trendy look of the 111mm aluminium reflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM

Product data

General Information	
Cap base	GX8.5 [GX8.5]
Operating position	UNIVERSAL [Any/Universal]
Life to 5% failures (nom.)	7500 h
Life to 10% failures (nom.)	8500 h
Life to 20% failures (nom.)	9500 h
Life to 50% failures (nom.)	11000 h
ANSI code HID	M139/O
Switching cycle	1000X

Light Technical	
Colour code	942 [CCT of 4200K]
Beam Angle (Nom)	40 °
Beam angle technical	36 °
Beam angle technical	45 °
Beam angle technical	27 °
Luminous flux (rated) (nom.)	2850 lm
Luminous intensity (min.)	6000 cd
Luminous intensity (nom.)	8000 cd
Beam description	Flood [Flood]
Colour designation	Cool White (CW)
Chromaticity coordinate X (nom.)	0.381
Chromaticity coordinate Y (nom.)	0.370
Correlated colour temperature (nom.)	4200 K
Color rendering index (nom.)	96
LLMF at end of nominal lifetime (nom.)	60 %
Luminous Flux in 90° Cone (Rated)	2800 lm

Operating and Electrical	
Power (Rated) (Nom)	73 W
Ignition supply voltage (max.)	198 V
Ignition supply voltage (min.)	198 V
Re-ignition time (min.) (max.)	15 min
Warm-up time to 60% light (nom.)	120 s
Ignition time (max.)	30 s
Voltage (Max)	114 V
Voltage (Min)	79 V

MASTERColour CDM-R111

Voltage (Nom)	92 V

Damage factor D/fc (max.)	0.3

Controls and Dimming	
Dimmable	no
Run-up time 90% (max.)	3 min

Mechanical and Housing	
Bulb finish	Reflector

Approval and Application	
Energy efficiency label (EEL)	B
Mercury (Hg) content (nom.)	6.3 mg
Energy Consumption kWh/1000 h	80 kWh


UV	
PET (NIOSH) (min.)	8 h/500lx

Product Data	
Full product code	871150021395210
Order product name	MASTERColour CDM-R111 70W/942 GX8.5 40D 1CT/6
EAN/UPC – product	8711500213952
Order code	21395210
Local Code	70CDMR11194240
Numerator – quantity per pack	1
Numerator – packs per outer box	6
Material no. (12NC)	928098105330
Net weight (piece)	0.095 kg
ILCOS Code	MRS/UB-70/942-H-GX8.5-111/88/40

Warnings and Safety

- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. 35W/830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing




CDM-R111 70W/942 40D

Product	D (max)	C (max)
MASTERColour CDM-R111 70W/942 GX8.5 40D 1CT/6	111 mm	95 mm

MASTERColour CDM-R111

Photometric data



© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.