
CLASSIC SURFACELINK

Stainless Steel Surface Mounted Anchor



- SurfaceLink Anchor suits a multitude of roof profiles.
- Surface mounted anchors must not be used for rope access (abseiling).
- Install using 10 Rivets (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip).
- The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent person that the structure is adequate.

STANDARDS
Complies with AS/NZS 1891.4.

WHAT AM I USED FOR?
An anchor point designed for use on metal roof sheet profiles where access to timber is difficult. Adjustable design to suit different roof profiles.



COMPLETE UNIT - PRODUCT CODE: HSURF001+RIVETS			Weight: 1.501kg
Product Parts	Description	Qty	Material
EYEBOLT-SURFACELINK	SurfaceLink Eyebolt	1	316 Stainless Steel
NUT LOCKING HEX	Locking Hex Nut	1	316 Stainless Steel
ADV-PLATE-SS-305-H	SurfaceLink Plate: 305mm	1	316 Stainless Steel
WASHER 70OD-SS	Washer: 70 OD	1	316 Stainless Steel
SPRING WASHER M16	Spring Washer: M16	1	316 Stainless Steel
NUT M16	Nut: M16	1	316 Stainless Steel
FOAM-TAPE 29 cm	Adhesive single sided tape	2	Foam
RIVETS_8mm(27)	Rivets: 8mm	10	Alum

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.
Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-51 Version: 16.0

Asia-Pacific/The Americas
info@safetylink.com

Europe/Africa/Middle East
europe.sales@safetylink.com

Northern Europe
uk.sales@safetylink.com

SafetyLink® Innovative Fall Protection

SCAN ME
www.safetylink.com

SCAN ME
Catalogue

SCAN ME
Anchor Layout Video

SCAN ME
Safety Centre Training

DATA SHEET

bsi ISO 9001 Quality Management Systems CERTIFIED FS 707792